

Phantom Antennas




TS0441M1B-xxx/PN



TS0411M1BE- xxx/M



TS0411M1B-xxx/M



TS0178-BkMag/x



TS0179-GP/N

Model#	Gain	Height (inches)	Diameter (inches)	Mount	Frequency Ranges (MHz)
VHF (132-174MHz)					
TS0411M1B-xxx/M	0 dBi	3.5	3.25	3/4" Mobile	142-160, 150-168, 156-172 (tuneable, 1.5MHz bandwidth)
TS0411M1BE-xxx/M	0 dBi	2.4	Oval	3/4" Mobile	144-148, 150-155, 155-160, 165-170
UHF (380-512MHz)					
TS0441M1B-xxx/M	1 dBi	3.3	1.5	3/4" Mobile	410-430, 430-450, 450-470, 470-490
TS0441M1B-xxx/PN	1 dBi	3.3	1.5	Permanent	
900MHz (928-960MHz)					
TS0491M1B-944/M	1 dBi	2.3	1.5	3/4" Mobile	928-960
TS0491M1B-944/PN	1 dBi	2.3	1.5	Permanent	
("xxx" designates the center frequency in MHz)					




Phantom Antennas


General Specifications

VSWR	<1.5:1
Maximum Power	100 watts
Impedance	50 Ohms
Termination	Mobile 3/4" mount Permanent hole mount (1.0 inch hole) with N female connector
Radiator	High impact plastic
Mounting Brackets	TS0177 – Permanent Mount TS0178 - Mobile Antenna Magnetic Mount TS0179 - Mobile Antenna Ground Plane Mast or Wall Mount


VSWR



TS0411M1B



TS0441M1B



TS0491M1B

